


FERRI A "U"

FERRI A "U" PROFILI NORMALI - EN 10279/02

| SPIGOLI VIVI | | | | | Momento resistenza W_x | Sezione cm ² | Peso per ml. Kg. |
|--------------|----|----|-----|-----|--------------------------|-------------------------|------------------|
| UNP | H | B | S | E | | | |
| 30 | 30 | 33 | 5,0 | 7,0 | 4,3 | 5,44 | 4,27 |
| 40 | 40 | 35 | 5,0 | 7,0 | 7,1 | 6,21 | 4,87 |
| 50 | 50 | 38 | 5,0 | 7,0 | 10,6 | 7,12 | 5,59 |
| 65 | 65 | 42 | 5,5 | 7,5 | 17,7 | 9,03 | 7,09 |



FERRI A "U"

FERRI A "U" PROFILI SPECIALI - UNI EU 54/81

| PROFILO | | | | | Sezione cm ² | Peso per ml. Kg. |
|---------|----|----|---|-----|-------------------------|------------------|
| UNS | H | B | S | E | | |
| 25 | 25 | 12 | 4 | 4 | 1,66 | 1,30 |
| 30 | 30 | 15 | 4 | 4,5 | 2,21 | 1,74 |
| 35 | 35 | 17 | 4 | 5 | 2,75 | 2,15 |
| 40 | 40 | 20 | 5 | 5,5 | 3,66 | 2,87 |
| 50 | 50 | 25 | 5 | 6 | 4,92 | 3,86 |
| 60 | 60 | 30 | 6 | 6 | 6,46 | 5,07 |

