


HEA

UNI 5397/78

PROFILO						Sollecitazione a flessione Carico totale uniformemente distribuito														
profil. mm	alt. H mm	largh. B mm	spess. ali mm	spess. asta mm	peso kg./m.	Distanza tra gli appoggi in metri														
						3	4	5	6	7	8	9	10	11	12	13	14	15		
100	96	99	8	5	16,7	30	22	18	14											
120	114	119	8	5	19,8	44	33	26	21	18										
140	133	138	8,5	5,5	24,7	65	48	38	31	26	23									
160	150	157	9	6	30,4	93	69	55	45	38	33	28	25							
180	172	177	10	6,5	35,5	124	92	73	60	51	44	38	34	30						
200	190	197	11	7	42,3	165	123	97	80	68	59	51	45	40	36					
220	211	217	11,5	7,25	50,5	218	163	129	107	91	78	68	61	54	49	44				
240	230	237	12,5	7,75	60,3	286	214	170	140	119	103	90	80	72	65	58	53	48		
260	250	257	13	8	68,2	354	265	210	174	148	128	113	100	90	81	73	67	61		
280	267	277	13,5	8,25	76,4	428	320	255	210	179	155	137	121	109	98	89	81	75		
300	289	297	14,5	8,25	88,3	535	400	318	263	224	194	171	152	137	124	112	103	94		
320	310	300	15,5	9	97,6	628	463	374	310	263	229	201	180	161	146	133	125	111		
340	330	300	16,5	9,5	105	713	533	424	352	300	260	229	204	184	166	152	139	127		
360	350	300	17,5	10	112	803	600	478	396	338	293	258	230	207	188	171	157	144		
400	390	300	19	11	125	981	734	585	485	413	359	318	283	255	231	211	193	179		
450	440	300	21	11,5	140	1233	922	735	610	520	453	400	357	322	292	267	245	226		
500	490	300	23	12	155	1510	1130	901	748	638	555	491	439	396	360	329	303	280		
550	540	300	24	12,5	166	1765	1321	1054	975	747	651	575	514	464	423	387	356	329		
600	590	300	25	13	178	2038	1525	1217	1011	863	752	665	595	538	489	450	413	382		
650	640	300	26	13,5	190	2328	1742	1390	1155	987	860	761	681	615	561	514	473	438		
700	690	300	27	14,5	204	2656	1989	1587	1319	1127	982	869	778	708	641	588	542	502		
800	790	300	28	15	224	3270	2448	1955	1625	1389	1211	1072	960	869	792	727	671	622		
900	890	300	30	16	252	4037	3023	2414	2007	1716	1496	1325	1188	1075	981	900	831	771		
1000	990	300	31	16,5	272	4766	3570	2851	2317	2027	1766	1567	1405	1272	1160	1066	985	914		





HEA

UNI 5397/78

PROFILO	Sollecitazione a compressione Carico massimo riferito all'altezza dei pilastri									
	Altezza pilastri in metri									
	3	3,5	4	4,5	5	5,5	6	6,5	7	8
alt. H mm	q.li									
100	184	159	137	111	91	75	63			184
120	251	227	201	179	156	128	108	92		
140	337	313	284	260	234	210	184	156	135	
160	440	411	385	355	323	296	269	245	213	
180	537	510	480	450	424	392	360	331	306	244
200	657	628	598	566	534	503	468	435	404	348
220	804	768	740	709	672	639	605	565	533	463
240	975	945	903	871	842	803	763	723	679	611
260	1120	1085	1044	1021	978	945	902	863	822	743
280	1276	1235	1197	1162	1128	1089	1045	1011	967	879
300	1488	1440	1406	1374	1323	1295	1250	1200	1169	1065
320	1645	1592	1555	1519	1463	1432	1382	1327	1292	1178
340	1765	1709	1669	1630	1570	1515	1483	1424	1378	1264
360		1828	1785	1744	1680	1620	1576	1523	1474	1352
400		2035	1987	1913	1870	1804	1754	1685	1620	1496
450			2225	2141	2094	2020	1951	1886	1814	1665
500			2450	2376	2323	2241	2164	2079	1987	1848
550			2788	2704	2626	2534	2432	2353	2251	2071

