



HEB

UNI 5397/78

PROFILO	Solllecitazione a compressione Carico massimo riferito all'altezza dei pilastri									
	Altezza pilastri in metri									
	3	3,5	4	4,5	5	5,5	6	6,5	7	8
alt. H mm	q.li									
100	228	198	170	138	113	93	78			
120	340	307	273	243	215	178	150	127		
140	468	433	395	358	323	290	261	221	190	
160	616	579	543	499	464	422	384	352	308	
180	774	736	697	653	611	568	525	481	446	359
200	961	919	873	827	781	735	686	641	595	518
220	1137	1095	1055	1011	958	910	861	818	759	671
240	1346	1305	1246	1203	1161	1116	1060	1003	953	852
260	1528	1480	1424	1393	1343	1289	1238	1184	1121	1024
280	1723	1668	1617	1581	1524	1480	1430	1374	1314	1201
300	1971	1924	1864	1821	1767	1716	1668	1601	1549	1428
320	2133	2081	2016	1970	1912	1857	1793	1732	1676	1545
340	2259	2187	2136	2087	2010	1967	1873	1835	1775	1637
360		2311	2257	2206	2125	2079	2006	1926	1876	1710
400		2531	2472	2379	2327	2244	2182	2096	2041	1861
450			2725	2622	2564	2473	2405	2310	2222	2051
500			2959	2870	2807	2707	2615	2511	2431	2232
550			3923	3224	3153	3042	2938	2823	2700	2468

